

# CLEANTECH 2000SCA

TECHNOLOGY FOR  
HAND HYGIENE



## The Only Fully Automated Handwashing Systems

Ideal for entrances to critical production areas that require fail-safe hygiene control over access; best for entrances into high risk, critical production areas.

### Features

- Two turnstile option for entrance & exit washing
- Optional Footwear Sanitizing Pan integration
- Stainless wall add-on for air dryer or paper towel
- Optional Integrated Air Curtain Dryer

### Turnstile options

- Right hand/left hand configuration
- Integrated stainless wall
- 2 turnstile configuration

### Cycle and Activation

Automatic, via infrared photo-optical sensor  
12-second wash and rinse cycle

### Handwash Compliance Monitor

Counts of handwash cycles, Optional resettable counter

### Water Consumption

0.6 gallons per hand wash cycle

### Self-Cleaning Feature

The handwashing system self-cleans 3x times per day (once per shift).

### Plumbing

2 each,  $\frac{3}{4}$ " male hose, hot and cold minimum 4 GPM, 40-100 PSI, 50 PSI optimum, water supply lines supplied

### Drain

Standard  $1\frac{1}{2}$ " drain stub, P-Trap to be supplied by facility  
Ideal drain height 18-22" from floor

### Solutions Gauge

Indicates Normal/Empty/Blocked Solution status

### Solutions Storage

2 – One gallon containers of Hand Soap  
1 – One gallon container of Self-Clean

### Hand Soap & Self-Clean

Required soap and self-clean chemical provided by Meritech (Other solutions will void warranty.)



### Electrical

System: 100-250 VAC 50/60 Hz, 300 W  
Turnstile: 120 VAC 50/60 Hz, 160 W

### Dimensions

47  $\frac{1}{2}$ " width x 43" depth x 48  $\frac{1}{2}$ " height

### Weight

335 lbs. (varies with options)

### Shipping Weight

450 lbs. (varies with options)

Made in the USA. Full 5-Year Parts Warranty.



Increases handwash compliance



Eliminates 99.98% of dangerous pathogens



Up to 5 handwashes per minute



Uses 75% less water



Produces 75% less waste

CleanTech Automated Handwashing are protected by the following U.S. Patents: U.S. Patent #5,265,628; #5,823,447; #7,607,442; #7,607,443; #7,617,830; #7,641,740; #7,659,824; #7,682,464; #7,698,770; #7,754,021; #7,754,022; #7,757,700; #7,758,701; other patents pending.

