

CLEANTECH ELF



CleanTech ELF Features

Ideal for healthcare, daycare and education, office break rooms and areas that need increased handwashing compliance without industrial specifications.

- Small footprint
- Wall mount, table mount, or counter mount options
- Ideal for healthcare and children's use
- K-Wash - kids cabinet available

Dimensions

17 1/4" width x 15 3/4" depth x 22 1/2" height

Weight

34 lbs. (varies with options)

Shipping Weight

49 lbs. (varies with options)

Cycle and Activation

Automatic, via infrared photo-optical sensor
12-second wash and rinse cycle

Handwash Compliance Monitor

Counts number of handwash cycles
Optional automatic reset of counter

Water Consumption

0.6 gallons per hand wash cycle

Electrical

100-250 VAC, 50/60 Hz, 300 W

Plumbing

2 each, 3/4" male hose, hot and cold minimum 4 GPM,
40-80 PSI, 60 PSI optimum

Drain

Standard 1 1/5" drain stub
P-Trap to be supplied by facility
Ideal drain height 18-22" from floor

Solutions Storage

1 - 32 oz. bottle or 1- one gallon option of Hand Soap

Solutions

Required solutions provided by Meritech
(Other solutions will void warranty)

Protective Modes

Current limited motor
Overheat auto shut off



CleanTech Automated Handwashing are pro-ctected by the following U.S. Patents: U.S. Patent #5,265,628; #5,823,447; #7,607,442; #7,607,443; #7,617,830; #7,641,740; #7,659,824; #7,682,464; #7,698,770; #7,754,021; #7,754,022; #7,757,700; #7,758,701; other patents pending.